

Full IP65 Stainless Steel Monitor

FIP-42W-CP

42" Stainless Steel Full-IP66/IP69K Display



Features:

1. 42" LED Backlight Display
2. Full-HD 1080p Input
3. Anti-Corrosion Stainless Design
4. Either P-cap multi-touch or AR glass in front
5. Full-IP66/ IP69K Protection

Specification

IP65 Input / Output :

- VGA : 1 x VGA
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI (optional)
- Video : NA
- USB : 1 x USB for touch (optional)
- Power Input : 1 x AC input

System Specification:

- Housing Material : Stainless Steel with deactivated coating for anti-corrosion
- Dimensions : 1041.0 x 633.5 x 80 (WxHxD) (mm)
- Weight : 38KG
- OSD Control : Auto video input detected
- Speakers : 2 x 2W speakers integrated (Optional)
- Mounting Type : VESA mount and 3x hangers

Power Specification:

- Power Input : 90~260V AC Input (IP65 Connector)
- Consumption : 80 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : 1x 1.8m AC Power Code (EU type)
- Power Adapter : No Power Adapter

Panel Specification :

- Size/ Type : 42" LCD (LED Backlight)
- Resolution : 1920 x 1080
- Brightness : 350 (cd/m²)
- Contrast Ratio : 1500 : 1 (typ.)
- Viewing Angle : -89~89 (H) ; -89~89 (V)
- Max. Colors : 16.7 M (8bits/color)
- Touch screen : P-cap multi-touch (USB)

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP Grade : Full- IP66/IP69K

Order Options :

- Touch Screen : IR touch screen (optional)
- High Brightness : 1,000 nits high brightness

Drawings

