

# LCD Touch Display

## LCH-65W

65" LCD (LED backlight) Full HD Monitor



### Specification

#### Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-I input
- HDMI : 1 x HDMI input
- Video : S-Video, Composite (optional)
- COM : 1 x RS232 for remote control (optional)
- Power Input : 1 x AC input

#### Power Specification:

- Power Adapter : N/A
- Consumption : 250 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : Provided by region

#### Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -10 deg. C to 70 deg. C
- Water/Dust proof : Front IP54
- Humidity : 10~90%RH (Non-condensing)

#### Panel Specification :

- Size/ Type : 65" LCD (LED backlight)
- Active Area (mm) : 1428.48 (H) x 803.52 (V)
- Pixel Pitch (mm) : 0.744 (H)x 0.744 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 5000 : 1 (typ.)
- Max. Colors : 1073.7 M (10-bit/colors)
- Brightness : 500 nits (cd/m<sup>2</sup>)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)

#### OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

#### Order Information :

- Touch : IR Touch Screen (optional)
- Speaker : 2W Speaker x2 (optional)
- High Brightness : 1,000 nits (optional)

### Drawings

