

Large Size LCD Display

LOF-55W-CP-FST

55" Monitor with P-cap multi-touch



Features:

1. Front side wall mount
(Mounting the machine from front into the wall, then topping on the front bezel .)
2. Stainless steel front bezel
3. P-cap multi-touch

Specification

Input Interface :

- | | |
|---------------|----------------------------|
| • VGA | : 1 x VGA D-Sub 15 pin |
| • DVI | : NA |
| • HDMI | : NA |
| • DP | : 1 x Display Port |
| • USB | : 1 x USB for touch screen |
| • Power Input | : 1 x AC input |

OSD :

- | | |
|----------------|---------------------------------|
| • OSD Input | : 5-key OSD buttons |
| • OSD Function | : Auto boot-up after powered in |

System :

- | | |
|---------------------|--|
| • Front Bezel | : Stainless steel front bezel |
| • I/O position | : I/O ports at top |
| • Mounting | : 1. Fringe mount: Open frame to the wall.
2. Front side clip: Front bezel topped on the monitor (by tension catch) |
| • Custom cable | : 5m external cables (power, USB, DP) |
| • Auto On/Off | : Auto boot up after powered-in |
| • In-wall thickness | : 100mm in-wall thickness |

Panel Specification :

- | | |
|--------------------|---------------------------------|
| • Size/ Type | : 55" LCD (LED backlight) |
| • Active Area (mm) | : 1209.6 (H) x 680.4 (V) |
| • Pixel Pitch (mm) | : 0.63 (H) x 0.63 (V) |
| • Resolution | : 1920 x 1080 @ 60Hz |
| • Contrast Ratio | : 5,000 : 1 (typ.) |
| • Max. Colors | : 1073.7M colors |
| • Brightness | : 450 nits (cd/m ²) |
| • Viewing Angle | : -89 ~ 89 (H); -89 ~ 89 (V) |
| • Touch | : P-cap multi-touch (USB) |

Power Specification:

- | | |
|-----------------|-----------------------------------|
| • Power Adapter | : N/A |
| • Consumption | : 300 W typical, normal operation |
| • Management | : VESA DPMS compliant |
| • Power Cord | : Provided by region |

Environment Tolerance:

- | | |
|-------------------------|-----------------------------|
| • Operating Temperature | : 0 deg. C to 45 deg. C |
| • Storage Temperature | : -20 deg. C to 70 deg. C |
| • Water/Dust proof | : Front IP54 |
| • Humidity | : 10~90%RH (Non-condensing) |

Drawings

