

Industrial LCD Touch Display

LPM-19R

19" (4:3) LCD Touch Monitor



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D (optional)
- HDMI : NA
- Video : S-Video, Composite (optional)
- COM : 1 x RS232 for touch (optional)
- Power Input : 1 x 3-pin AC input

Power Specification:

- Power Input : AC Input
- Consumption : 45 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : No Power Cord

Environment Tolerance:

- Operating Temperature : -5 deg. C to 50 deg. C
- Storage Temperature : -40 deg. C to 70 deg. C
- IP Level : Front IP54

Panel Specification :

- Size/ Type : 19" (4:3) LCD (LED backlight)
- Active Area (mm) : 376.32(H) x 301.06 (V)
- Pixel Pitch (mm) : 0.294(H)x 0.294(V)
- Resolution : 1280 x 1024@ 60Hz
- Contrast Ratio : 1000 : 1 (typ.)
- Max. Colors : 16.7M (6 bits + FRC)
- Brightness : 350 nits (cd/m²)
- Viewing Angle : -85 ~ 85 (H); -80 ~ 80 (V)
- Touch Screen : 5-wire resistive touch screen

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Information :

- Optical Bonding : Touch Glass and Panel Bonded (for optional)
- Power Input : 9~36V DC Input (for optional)

Drawings

