

Industrial LCD Touch Display

LPM-22W-CP

21.5" Wide Screen / Front IP65 / Panel Mount Monitor



Specification

Input Interface :

- VGA : 1 x VGA
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI (optional)
- Video : S-Video, Composite (optional)
- USB : 1 x USB for touch (optional)
- Power Input : 1 x DC input

Keypad :

- OSD buttons : 5-key OSD buttons

Power Specification:

- Power Input : 9~36V DC Input
- Consumption : 25 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : N/A
- Power Adapter : N/A

Panel Specification :

- Size/ Type : 21.5" LCD (LED backlight)
- Active Area (mm) : 476.64(H) x 268.11 (V)
- Pixel Pitch (mm) : 0.248(H)x0.248(V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 3000 : 1 (typ.)
- Max. Colors : 16.7M (8 bits + FRC)
- Brightness : 250 nits (cd/m²)
(1,000 nits for optional)
- Viewing Angle : -85 ~ 85 (H); -80 ~ 80 (V)
- Touch Screen : 5-wire resistive touch or P-cap multi-touch

Environment Tolerance:

- Operating Temperature : 0 deg. C to 55 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- IP Grade : Front IP65

Accessory:

- Cable : 1 x 1.5m VGA cable
(provided by I/O) 1 x 1.5m DVI cable
1 x 1.5m Power cable
- Driver CD : 1 x Driver CD for touch screen
(Resistive touch)

Order Information :

- Touch : 5-wire resistive touch
Or P-cap touch screen (USB)
- Power Input : 12V DC Input or 9~36V DC Input
(Terminal Bock)

Drawings

