

# 1U Rack Mount Drawer – 19” 1U Rackmount

## LRK-19R-1U

19” LCD (LED Backlit), 1U Rack Mount Drawer



### Specification

#### Input Interface :

• VGA	: 1 x VGA D-Sub 15 pin
• DVI	: 1 x DVI-D Input
• HDMI	: NA
• Video	: Component AV (optional)
• HD-SDI	: 1 x HD-SDI Input (optional)
• Power Input	: 1 x AC input (100~240V Universal)
• Serial Ports	: 1 x RS232 remote control (optional)
• PS/2	: N/A
• USB	: 1 x USB for touch screen (optional)
• Keyboard	: N/A
• Keypad	: N/A

#### System Spec.:

• Housing	: Heavy duty steel
• Lock	: 2 x Screw knob for Screen Lock
• Mounting	: For 19” Rack mount with 530 ~ 600mm in depth
•Weight	: 12KG

#### Panel Specification :

• Size/ Type	: 19” LCD (LED backlight)
• Active Area (mm)	: 376.32(H) x 301.06 (V)
• Pixel Pitch (mm)	: 0.294(H)x0.294(V)
• Resolution	: 1280 x 1024@ 60Hz
• Contrast Ratio	: 1000 : 1 (typ.)
• Max. Colors	: 16.7M (6 bits + FRC)
• Brightness	: 250 nits (cd/m <sup>2</sup> )
• Viewing Angle	: -85 ~ 85 (H); -80 ~ 80 (V)

#### OSD :

• OSD Input	: 5-key OSD buttons
• OSD Function	: Contrast, Color, Position, Auto-adjustment, Factory Settings

#### Environment Tolerance:

• Operating Temperature	: 0 deg. C to 50 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C
• Power Consumption	: 20 Watts (Typically)

#### Order Information :

• Speaker	: 2W Speaker x2 (optional)
• High Brightness	: 1000 nits (optional)

### Drawings

