

LCD Touch Display

LRK-21R

21.3" Console Mount LCD Terminals



Specification

I/O Interface :

• BNC	: N.A. (optional)
• VGA	: 1 x VGA (Optional)
• DVI	: 1 x DVI-D
• HDMI	: 2 x HDMI
• Display Port	: 1 x DP Input, 1x DP Output(Daisy Chain)
• Power Input	: 1 x AC Input

OSD :

• OSD Input	: 5 -key OSD buttons
• OSD Function	: Contrast, Color, Position, Auto-adjustment, Factory Settings

Power Specification:

• Power Adapter	: N/A
• Consumption	: 65 W typical, normal operation
• Input	: 100~240V AC Input
• Power Cord	: N/A

Weight/Dimensions :

• Weight	: 9.3KG (Identity)
• Dimensions (mm)	: 533.4(L) x 443.7(H) x 95.5(D)

Panel Specification :

• Size/ Type	: 21.3" (4:3) LCD (LED backlight)
• Active Area (mm)	: 432(H) x 324(V)
• Pixel Pitch (mm)	: 0.270 (H)x 0.270 (V)
• Resolution	: 1600 x 1200 @ 60Hz
• Contrast Ratio	: 1200 : 1 (typ.)
• Max. Colors	: 16.7M colors
• Brightness	: 300 nits (cd/m ²)
• Viewing Angle	: -89 ~ 89 (H); -89 ~ 89 (V)
• Glass	: AR protective glass

Environment Tolerance:

• Operating Temp.	: -25 deg. C to 60 deg. C
• Storage Temp.	: -40 deg. C to 80 deg. C
• Operating Humidity	: 5% to 95% (Non Condensing)
• IP level	: Front-IP65
• EMI	: MIL-STD-461F Compliance (optional)
• Vibration	: MIL-STD-810G Method 514.6C-3
• Shock	: MIL-STD-810G Method 516.6
• Humidity	: MIL-STD-810G Method 507.5-7
• Salt Fog	: MIL-STD 810G, Method 509.5
• IP Level	: Front IP65

Drawings

