

Full IP66 Stainless Steel Monitor

FIP-32W-CP

32" Stainless Steel Full-IP66/IP69K Display



Features:

1. 32" Full-HD 1080p Input
2. Anti-Corrosion Stainless Design
3. Either P-cap multi-touch or AR glass in front
4. Full-IP66/IP69K Protection

Specification

IP66 Input / Output :

- VGA : 1 x VGA
- DVI : 1 x DVI-D (optional)
- HDMI : 1 x HDMI (optional)
- Video : NA
- USB : 1 x USB for touch (optional)
- Power Input : 1 x AC input

System Specification:

- Housing Material : Stainless Steel with deactivated coating for anti-corrosion
- Dimensions : 822 x 510 x 85 (WxHxD) (mm)
- Weight : 32KG
- OSD Control : Auto video input detected
- Speakers : 2 x 2W speakers integrated (Optional)
- Mounting Type : VESA mount

Power Specification:

- Power Input : 90~260V AC Input (IP66 Connector)
- Consumption : 40 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : 1x 1.8m AC Power Code (EU type)
- Power Adapter : No Power Adapter

Panel Specification :

- Size/ Type : 32" LCD (LED backlight)
- Active Area (mm) : 698.4 (H) x 392.85 (V)
- Pixel Pitch (mm) : 0.3638 (H)x0.3638 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 3000 : 1 (typ.)
- Max. Colors : 16.7M colors
- Brightness : 450 nits (cd/m²)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)
- Touch : P-cap multi-touch (USB)

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP Grade : Full- IP66/ IP69K

Order Options :

- Touch Screen : IR touch screen (optional)
- High Brightness : 1,000 nits high brightness

Drawings

